

## 90 Minute Fire Rated Under-Bench Cabinet Tested to EN & FM Standards - 792T

Manufactured in the EU to comply with EN and FM standards this cabinet is built using a double wall construction method: Thermal insulation is sandwiched between an outer sheet steel shell and an inner melamine-based wood shell and the exterior is finished in a high quality epoxy coating RAL 9010 white and is fitted with safety labelling in accordance with EN 14470-1.

The cabinet comes complete with a removable containment sump and an earthing link, the self closing door (can be kept open) is fitted with a fusible link, which if the temperature rises above 47°C will break and allow the door to close automatically.

Ventilation is provided by means of 100mmØ air inlet/air outlet ducts which provide natural ventilation or can be connected to a forced ventilation/filtration system. The ducts are protected by thermos-fuse seals that automatically shut the system in the event if a fire. Likewise the door is protected by thermo-expanding seals and is fitted with a cylinder lock.



SPECIFICATION	
Size	670mm H x 1135mm L x 615mm D
Storage capacity	60ltr
No of doors	1 door/drawer
Complete with	1 containment sump
Maximum load per shelf	50kg
Unit weight	240kg
Colour	white

Standards: EN14470-1 - Fire safety storage cabinets - Safety storage cabinets for flammable liquids, EN 1363-1 Fire resistance tests - General requirements & FM 6050 Flammable (Ignitable) Liquids Equipment.



### EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049