

CoSHH Security Cupboard Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Shelves Supplied</u>	<u>Sump Capacity</u>
1800mm	900mm	460mm	3	14 Litres
1800mm	1200mm	460mm	3	18 Litres
1200mm	900mm	460mm	2	14 Litres
1200mm	1200mm	460mm	2	16 Litres
900mm	460mm	460mm	1	7 Litres

Cupboard Construction:

- 1.2mm mild steel, seam-welded carcass construction
- Full length piano hinges
- Rust resisting galvanised shelves
- Integral liquid-tight sump fitted at the bottom of the cupboard
- Door aperture has return bends to eliminate open gaps
- Delivered assembled
- Reaction to Fire Classification EN 13501-1 – documents available
- Supplied with one warning label
- Seven lever safe lock and an anti-pick locking mechanism
- Extra Shelves are available with the CoSHH Security Cupboard range

Sump Construction:

- Material: 1.2mm Mild Steel
- Fully welded seams
- Sump Integral

Cupboard Door Construction:

1.2mm thick steel door with full length welded/riveted continuous hinge, incorporating retaining rail to prevent hinge/door removal.

Two point espagnolette locking mechanism secures both doors into carcass. Fitted with a 7 lever Lowe & Fletcher 2802 anti-pick safe lock.

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Carcass powder coated with a special paint – **Dark Grey RAL 7024**

Carcass & Door colour:

Dark Grey	RAL 7024
-----------	----------

Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)



RICHARDSONS
MAKING WORKSPACE WORK

6 Collingwood Court
Riverside Park
Middlesbrough TS2 1RP

Tel: 01642 242228 | Fax: 01642 242259

www.richardsonsuk.co.uk | sales@richardsonsuk.co.uk