

## Drum Store - DS2P

A pressed steel welded body construction provides the structural strength for this unit, while the roof which is fitted with lifting eyes is manufactured from mild steel. The two hinged doors are constructed from mild steel and are fitted with a rod and level lock with a keyed handle.

Constructed from mild steel, the sump is fully seam welded and fitted with pallet support beams for the pallet to sit directly on to and pallets on the upper level sit directly on to a steel support frame. The sump as you would expect complies fully with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface. This model can hold up to 8 x 205ltr drums (2 pallet location) across two levels and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

### Chargeable Options:

- Air vents
- Galvanised steel grid mesh
- Galvanised steel pallet channels

Please notify us at the time of ordering if you require any of these options.



SPECIFICATIONS	
Size	1450mm L x 1450mm (plinth) 1550mm W x 2935mm H at the highest point on the unit
Lower level clear space	1187mm H
Upper level clear space	1188mm H
Nº of containers	8 x 205ltr - vertical
Sump capacity	450ltr
Colour	Green RAL 6029
Tare weight	600kg
Type of doors	2 hinged
Type of door lock	Rod & lever with keyed handle
Access aperture	1320mm W x 2480mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.