

ECLIPSE PLASTIC PLUS

THE STRENGTH OF STEEL WITH THE CORROSION RESISTANT QUALITIES OF PLASTIC

- ⇒ **Vented or solid design-** removable polypropylene shelf panels
- ⇒ **Highly Resistant-** protective antibacterial epoxy coating
- ⇒ **Strong and robust-** Up to 360kg shelf load capacity
- ⇒ **Quick and easy to assemble-** bolt free and no specialist tools required
- ⇒ **Fully adjustable-** shelf heights every 25mm
- ⇒ **Temperature resistant-** from -29°C to +88°C
- ⇒ Available in 48 size combinations
- ⇒ **Highly Durable-** guaranteed for up to 10 years



ECLIPSE PLASTIC PLUS

THE STRENGTH OF STEEL WITH THE CORROSION RESISTANT QUALITIES OF PLASTIC

Shelf Loading (4-tier unit)

Shelf Length	Static Units	With 75mm castors	With 100mm castors	With 120mm castors
Up to 1220mm	360kg per shelf	210kg per bay	240kg per bay	300kg per bay
Over 1220mm	280kg per shelf	210kg per bay	240kg per bay	300kg per bay

Pitch Levels

1625mm high unit

No. of shelves	3	4	5	6	7	8	9	10	11	12
Floor to Bottom Shelf	87mm	87mm	87mm	87mm	87mm	87mm	87mm	240mm	87mm	215mm
Between Shelves	730mm	470mm	350mm	270mm	220mm	3 x 195mm 4 x 170mm	4 x 170mm 4 x 145mm	120mm	120mm	95mm

1820mm high unit

Floor to Bottom Shelf	87mm	67mm	67mm	87mm	110mm	67mm	87mm	190mm	87mm	87mm
Between Shelves	820mm	540mm	385mm	310mm	235mm	210mm	170mm	130mm	1x110mm 9x130mm	100mm

2130mm high unit

Floor to Bottom Shelf	87mm	87mm	87mm	87mm	87mm	87mm	87mm	67mm	67mm	67mm
Between Shelves	970mm	665mm	460mm	360mm	5x290mm 1x310mm	5x230mm 2x260mm	210mm	185mm	160mm	4x160mm 7x130mm

Cleaning Process

Shelf panels can be removed and cleaned in a dishwasher. Frames should be wiped clean with a dry cloth. If a damp clean is required, ensure the area is dried well. Do not use corrosive or abrasive cleaners on the frames.